

Ref. 1CRUF0

Cut - Precision Work

Dry Environment



The +

COVERPERF DURABILITY: Ultra high abrasion resistance
Crotch between thumb and index
Highest level of cut protection: CUT F
Dexterity
Good breathability
Touchscreen

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CRUF00007	7	5	50
1CRUF00008	8	5	50
1CRUF00009	9	5	50
1CRUF00010	10	5	50
1CRUF00011	11	5	50
1CRUF00012	12	5	50

SALES PACKAGING

Hangable individual polybag

DESCRIPTION

Black seamless support from HDPE, polyamide, elastane,
Black nitrile foam palm coating, 13 gauge,
Nitrile patch reinforcement between thumb and index,
Knitted wrist.

SECTORS

Light Industries
Maintenance
Transport (excluding manufacturing) and logistics

APPLICATIONS

Handling in dry or slightly oily area with mechanical risks, for glass, automotive or aeronautical industry, injection moulding, construction, logistics, packaging...

TECHNICAL FEATURES



Gauge 13

Color	Black
Color 2	Black
Shape	Glove
Gloves environment	Dry, slightly oily environment
Glove type	Seamless knitting
Support material	HDPE polyester spandex
Coating level	Palm
Material of coating	Nitrile
Coating finition	Foam
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/07/20/1925

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



4.X.4.3.F.

Protection from mechanical risks

ANSI



Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

COVERPERF - Durability/Abrasion resistance



Gloves tested in a certified laboratory (CTC) offering excellent resistance to abrasion. Resistance above 20 000 cycles, compared to 8000 cycles for standard EN 388

RETAILER STAMP

MAJ 10/07/2023