

Industrial / Spectacles / 506 UP

506 UP - Solar G15

Code: 506U.04.04.05

Date: 14-09-26

1/2

506 UP presents technical and aesthetic improvements. The panoramic and wrapping lens is available with Vanguard Plus coating for superior performance in all conditions. The temples with rubber tips and adjustable in length and inclination, the total adaptability of the nose pad and the new range of vibrant colors allow a high degree of customisation of the device.



Frame mark (EU)

506U U 166 FT CE

Lens mark (EU)

2C-3/5-3.1 U 1 FT CE

Frame technology

Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal

Conditions of use

High brightness

Lens technology

Anti-Scratch, UV400

Lens color

Green

Lens material

Polycarbonate

Frame color

Black/Green

Standards

EN166, EN170, EN172

Scale number

(2C-3), (5-3.1)

Mechanical resistance

Low energy impact (F)

Optional requirements

Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (1)

Weight

25g

>> <https://www.univetsafety.com/en/products/safety/spectacles/506-up/506-up-solar-g15/>



01.

TEMPLES ADJUSTABLE IN LENGTH
AND INCLINATION

02.

OPTIMAL COMFORT AND FIT
THANKS TO THE SOFT ADJUSTABLE
NOSE PAD

03.

PANORAMIC AND WRAPAROUND
LENS FOR A BETTER SIDE
PROTECTION

04.

SOFT TERMINAL TIPS TO ELIMINATE
LOCAL PRESSURE

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163