

Industrial / Spectacles / 555

555 - Clear

Code: 555.03.00.00

Date: 14-09-26

1/2

**Frame mark (EU)**

U EN166 FT CE

Lens mark (EU)

2C-1.2 U 1 FT K N CE

Frame technology

Rubber Terminal

Conditions of use

Standard brightness, Low brightness

Lens technology

Anti-Scratch (K), Anti-Fog (N), UV380

Lens color

Clear

Lens material

Polycarbonate

Frame color

Black/Green

Standards

EN166, EN170

Scale number

(2C-1.2)

Mechanical resistance

Low energy impact (F)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (1)

Weight

32g

>> <https://www.univetsafety.com/en/products/safety/spectacles/555/555-clear/>



01.

IT OFFERS A WIDE COVERAGE AREA

02.

INTEGRATED SIDE SHIELDS

03.

OVERMOLDED TEMPLES MADE OF
NON-SLIP RUBBER

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163