

Industrial / Goggles / 6X3

6X3 - Clear Ultra Lens

Code: 042117

Date: 16-09-26

1/2

Univet Research and Development department designed 6X3 goggle with the intention of combining a higher level of protection and an innovative style. The result is an amazing product for performance and design, with a panoramic lens offering excellent peripheral vision that can be used comfortably with any corrective eyewear, assuring a perfect fit.

**Lens mark (EU)**

2C-1.2 U 1 BT 9 K N CE

Conditions of use

Standard brightness, Low brightness

Fields of use

Molten metals and hot solids (9)

Lens technology

Anti-Scratch + Anti-Fog (KN - Vanguard ULTRA), UV380

Lens color

Clear

Lens material

Polycarbonate

Standards

EN166, EN170

Scale number

(2C-1.2)

Mechanical resistance

Medium energy impact (B)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (1)

>> <https://www.univetsafety.com/en/products/safety/goggles/6x3/6x3-clear-ultra-lens/>



01.

LENS INTERCHANGE SYSTEM

The patent lens interchange system allows the user to quickly replace the lens based on visibility conditions.

02.

SOFT RUBBER GASKET

Certified according to EN166 standard, point 3 and 4 for protection against droplets, splashes and large dust particles.

03.

OVERSPEC FUNCTION

The 6X3 goggle is designed for perfect integration with the prescription glasses, ensuring total protection.

04.

ADVANCED PROTECTION

The 6X3 goggle guarantees a correct interaction with the filtering half masks, maintaining an unaltered performance.

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163