

Ref. **9ADAH**

Multipurpose

High

High shoes



S2

SR

FO



PURCHASE PACKAGING

Ref.	Size	Carton
9ADAH34	34	10
9ADAH35	35	10
9ADAH36	36	10
9ADAH37	37	10
9ADAH38	38	10
9ADAH39	39	10
9ADAH40	40	10
9ADAH41	41	10
9ADAH42	42	10
9ADAH43	43	10
9ADAH44	44	10
9ADAH45	45	10
9ADAH46	46	10
9ADAH47	47	10
9ADAH48	48	10
9ADAH49	-	

Some sizes may only be available in certain countries

DESCRIPTION

- * leather safety boots
- * steel toe cap for protection against falling objects
- * oil resistant, antistatic, dual density PU sole, SRC-level anti-slip properties, tested on wet ceramic and steel surfaces
- * padded ankle and watertight tongue, green seams
- * S

APPLICATIONS

Luggage handler, Delivery driver, ...

TECHNICAL FEATURES

Color	Black	Front bumper	
Color 2	Green	Closing	Lacing closure
Upper	Grain leather	Lining	Moisture wicking non-woven membrane
Toecap	Steel		
Midsole	PU	Defined heel	
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the over-shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the over-shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/01/24/0027 EXT 01/01/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance