

Ref. **9ALBA**

Specialties

High

High shoes



S2

0%
METAL

The +

* excellent ventilation, water vapor permeable properties * SRC non-slip * strong plastic lacing guides, completely metal-free, light weight, for sanitary, food industry work

PURCHASE PACKAGING

Ref.	Size	Carton
9ALBA35	35	10
9ALBA36	36	10
9ALBA37	37	10
9ALBA38	38	10
9ALBA39	39	10
9ALBA40	40	10
9ALBA41	41	10
9ALBA42	42	10
9ALBA43	43	10
9ALBA44	44	10
9ALBA45	45	10
9ALBA46	46	10
9ALBA47	47	10
9ALBA48	48	10

Some sizes may only be available in certain countries

DESCRIPTION

- * breathable microfiber upper
- * excellent water repellent and water vapor permeability
- * composite (CK) toecap
- * antistatic, oil-proof, anti-slip white PU soles with shock-absorbing heels
- * SRC-level anti-slip protection, tested on wet ceramic and metal s

SECTORS

Chemical & pharmaceutical industries

Light Industries

Food-processing industry

TECHNICAL FEATURES

Color	White
Upper	Microfiber
Toecap	Composite
Midsole	PU
Outsole	PU
Main assembly	Injected
Closing	Lacing closure
Lining	Moisture wicking non-woven membrane

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the over-shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the over-shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00373736 Issue 2

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper