

Ref. **9BOUL70**

Multipurpose

Low

Low shoes



The +

- * Style inspired by fashion sneakers.
- * Waterproof upper.
- * Insole foam with pads: comfort.
- * EVA / Rubber outsole: cushion and lightness.

PURCHASE PACKAGING

Ref.	Size	Carton
9BOUL70036	36	6
9BOUL70037	37	6
9BOUL70038	38	6
9BOUL70039	39	6
9BOUL70040	40	6
9BOUL70041	41	6
9BOUL70042	42	6
9BOUL70043	43	6
9BOUL70044	44	6
9BOUL70045	45	6
9BOUL70046	46	6
9BOUL70047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

BOULDER combines protection, aesthetics and modernity. Its pull-up leather upper gives it an elegant style and protection against rain (WRU).

With a cushioned insole, BOULDER is also comfortable to wear.

The EVA/Rubber outsole is oil resistant and slip resistant on tile and metal floors.

SECTORS

Light Industries

Maintenance

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

mason, roofer, ramp agent, baggage handler, works foreman, docker

TECHNICAL FEATURES

Color	Brown	Main assembly	Cemented
Weight	501 g	Closing	Lacing closure
Upper	Pull-up leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		
Insole	Foam with pads		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/01/22/0045

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)