

Ref. **9BUBO**

Specialties

Low

Sandals

S1



The +

- * Open shoe to be protected without suffering from heat.
- * Breathable upper and lining.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9BUBO35	35	10
9BUBO36	36	10
9BUBO37	37	10
9BUBO38	38	10
9BUBO39	39	10
9BUBO40	40	10
9BUBO41	41	10
9BUBO42	42	10
9BUBO43	43	10
9BUBO44	44	10
9BUBO45	45	10
9BUBO46	46	10
9BUBO47	47	10
9BUBO48	48	10

Some sizes may only be available in certain countries

DESCRIPTION

BUBO is an open shoe in micro-perforated microfiber. It protects without suffering from heat. Its breathable 3D mesh lining increases its breathability. Its round heel allows more comfortable driving. This model is equipped with a composite toecap. Its polyurethane outsole in double density is oil and slip resistant.

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	White	Main assembly	Injected
Color 2	Grey	Closing	Scratch closure
Weight	424 g	Lining	Breathable 3D mesh
Upper	Microfiber		
Toecap	Composite		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/23/1933 EXT 01/11/23

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

EN ISO 20345:2022

Safety shoes

S1

S1 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance