

Ref. **9CARL60**

Indoor and dry environments

Low

High shoes



S1

SR

FO



The +

*Defined heel for better safety especially on ladders.

*PU2D injected outsole: comfort and adherence.

PURCHASE PACKAGING

Ref.	Size	Carton
9CARL60035	35	6
9CARL60036	36	6
9CARL60037	37	6
9CARL60038	38	6
9CARL60039	39	6
9CARL60040	40	6
9CARL60041	41	6
9CARL60042	42	6
9CARL60043	43	6
9CARL60044	44	6
9CARL60045	45	6
9CARL60046	46	6
9CARL60047	47	6
9CARL60048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

- * Protective shoes S1 with cowhide uppers
- * Antistatic, oil- and acid-proof, SRC anti-slip protecting, flexible double-layer PU soles, steel toe guard against falling objects, broadened toe caps
- * Ankles and watertight tongues sponge-filled all along

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Color 2	Yellow	Closing	Lacing closure
Weight	525 g	Lining	Moisture wicking non-woven membrane
Upper	Grained leather		
Toecap	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/23/1304 EXT 03/10/23

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S1

Safety shoes

S1 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance