

Ref. **9CARL60**

Indoor and dry environments

Low

High shoes



S1



### The +

\*Defined heel for better safety especially on ladders.

\*PU2D injected outsole: comfort and adherence.

### PURCHASE PACKAGING

Ref.	Size	Carton
9CARL60035	35	6
9CARL60036	36	6
9CARL60037	37	6
9CARL60038	38	6
9CARL60039	39	6
9CARL60040	40	6
9CARL60041	41	6
9CARL60042	42	6
9CARL60043	43	6
9CARL60044	44	6
9CARL60045	45	6
9CARL60046	46	6
9CARL60047	47	6
9CARL60048	48	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

- \* Protective shoes S1 with cowhide uppers
- \* Antistatic, oil- and acid-proof, SRC anti-slip protecting, flexible double-layer PU soles, steel toe guard against falling objects, broadened toe caps
- \* Ankles and watertight tongues sponge-filled all along

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Color 2	Yellow	Closing	Lacing closure
Weight	525 g	Lining	Moisture wicking non-woven membrane
Upper	Grained leather		
Toecap	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00381071

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1

SRC

## Safety shoes

**S1** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol