

Ref. **9DESA**

Synthetic Boots

PVC

Boots



S5



The +

- \* Excellent grip thanks to an oil resistant outsole.
- \* Waterproof.
- \* Energy absorption in the heel area.

### PURCHASE PACKAGING

| Ref.    | Size | Carton |
|---------|------|--------|
| 9DESA36 | 36   | 8      |
| 9DESA37 | 37   | 8      |
| 9DESA38 | 38   | 8      |
| 9DESA39 | 39   | 8      |
| 9DESA40 | 40   | 8      |
| 9DESA41 | 41   | 8      |
| 9DESA42 | 42   | 8      |
| 9DESA43 | 43   | 8      |
| 9DESA44 | 44   | 8      |
| 9DESA45 | 45   | 8      |
| 9DESA46 | 46   | 8      |
| 9DESA47 | 47   | 8      |

*Some sizes may only be available in certain countries*

### DESCRIPTION

Steel toecap  
Steel antipenetration sole  
External sole in black PVC  
Green PVC upper  
White polyester lining

### SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

## TECHNICAL FEATURES

|                         |             |
|-------------------------|-------------|
| Color                   | Green       |
| Color 2                 | Black       |
| Weight                  | 944 g       |
| Upper                   | PVC         |
| Toecap                  | Steel       |
| Puncture resistant sole | Steel       |
| Outsole                 | PVC nitrile |
| Lining                  | Polyester   |

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE-2790-135/2021

Delivered by ASSOCIAÇÃO PORTUGUESA DOS INDUSTRIAIS DO CALÇADO - COMPONENTES-ARTIGOS DE PELE E SEUS SUCEDÂNEOS (APPICAPS) (2790) RUA ALVES REDOL - 372 4050-040 PORTO - Portugal



EPI CAT. II

EN ISO 20345:2011

S5

SRA

Safety shoes

**S5** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol