

Ref. **9GANLEX20**

Multipurpose

Low

Low shoes



S3



PURCHASE PACKAGING

Ref.	Size	Carton
9GANLEX20/36	36	
9GANLEX20/37	37	
9GANLEX20/38	38	
9GANLEX20/39	39	
9GANLEX20/40	40	
9GANLEX20/41	41	
9GANLEX20/42	42	
9GANLEX20/43	43	
9GANLEX20/44	44	
9GANLEX20/45	45	
9GANLEX20/46	46	
9GANLEX20/47	47	
9GANLEX20/48	48	

Some sizes may only be available in certain countries

DESCRIPTION

- * antistatic safety footwear, with water repellent, breathable nappa leather upper
- * extremely flexible, oil and acid resistant, advanced SRC anti-slip, dual density PU sole with energy absorbent heel
- * composite toe cap, flexible, penetration resistant,

SECTORS

Mechanicals constructions

Light Industries

Manufacture of electrical and electronic equipment and machines

Maintenance

Construction - finishing work

DIY

TECHNICAL FEATURES

Color	Beige	Closing	Lacing closure
Upper	Nubuck leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole			
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These over-shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the over-shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the over-shoes by using brushes, cleaning clothes.

STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol