

Ref. **9GANLEX32**

Specialties

Low

Low shoes



The +

SB WRU E P FO SRC shoes

*Protection against electric shocks of up to 1000 V, 50 Hz frequency alternating voltage, in dry conditions.

*PU2D outsole: flexible, energy absorbing, heat-proof up to 180°C.

PURCHASE PACKAGING

Ref.	Size	Carton
9GANLEX32/36	36	6
9GANLEX32/37	37	6
9GANLEX32/38	38	6
9GANLEX32/39	39	6
9GANLEX32/40	40	6
9GANLEX32/41	41	6
9GANLEX32/42	42	6
9GANLEX32/43	43	6
9GANLEX32/44	44	6
9GANLEX32/45	45	6
9GANLEX32/46	46	6
9GANLEX32/47	47	6
9GANLEX32/48	48	6

Some sizes may only be available in certain countries

DESCRIPTION

- * electrician shoes: protection against electric shocks of up to 1000 V, 50 Hz frequency alternating voltage, in dry conditions (test voltage 10000 V)
- * cow-hide uppers of excellent water-proof and steam permeation properties
- * flexible, energy absorbing,

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry
- Construction - finishing work

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	545 g	Closing	Lacing closure
Upper	Grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Textile and foam, removable		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 2/2020

Delivered by MÁDI ÉS TSA KFT. TANÚSÍTÓ SZERVEZET (1556) Wysocki utca 1. 1155 BUDAPEST Hungary



EPI CAT. III

EN ISO 20345:2011

SB

SRC

Safety shoes

SB Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol