

Ref. **9MALI**

Specialties

Low

Low shoes



O2



The +

- * completely metal-free
- * SRC anti-slip
- * without white toe protector
- * removable, antistatic, sweat-absorbing, energy-absorbing insole with comfortable textile surface

PURCHASE PACKAGING

| Ref. | Size | Carton |
|---------|------|--------|
| 9MALI35 | 35 | 10 |
| 9MALI36 | 36 | 10 |
| 9MALI37 | 37 | 10 |
| 9MALI38 | 38 | 10 |
| 9MALI39 | 39 | 10 |
| 9MALI40 | 40 | 10 |
| 9MALI41 | 41 | 10 |
| 9MALI42 | 42 | 10 |
| 9MALI43 | 43 | 10 |
| 9MALI44 | 44 | 10 |
| 9MALI45 | 45 | 10 |
| 9MALI46 | 46 | 10 |
| 9MALI47 | 47 | 10 |
| 9MALI48 | 48 | 10 |

Some sizes may only be available in certain countries

DESCRIPTION

- * breathable water repellent microfiber upper
- * antistatic, oil-proof, anti-slip white dual density PU/PU soles with shock-absorbing heels
- * SRC-level anti-slip protection, tested on wet ceramic and metal surfaces
- * removable, antistatic, sweat-absorbent,

SECTORS

Light Industries

Food-processing industry

Services and distribution

TECHNICAL FEATURES

| | | | |
|---------|--|--------|-------------------------------------|
| Color | White | Lining | Moisture wicking non-woven membrane |
| Upper | Microfiber | | |
| Midsole | PU | | |
| Outsole | PU | | |
| Insole | removable, antistatic, sweat-absorbing, energy-absorbing insole with a comfortable textile surface | | |
| Closing | Lacing closure | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00373727

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20347:2012

O2

SRC

Working shoes

O2 Minimal properties (=résistance to friction, tearing and slip resistance, water vapor permeability)+closed heel area +energy absorption in the heel area (E) + antistatic properties (A)+ water resistant upper

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol