

Ref. **9MOLL**

Multipurpose

Low shoes



The +

- \* Lightweight and comfortable for use all day long.
- \* Breathable upper and lining.
- \* Sporty looking.

### PURCHASE PACKAGING

Ref.	Size	Carton
9MOLL37	37	
9MOLL38	38	5
9MOLL39	39	5
9MOLL40	40	10
9MOLL41	41	10
9MOLL42	42	10
9MOLL43	43	10
9MOLL44	44	10
9MOLL45	45	10
9MOLL46	46	5
9MOLL47	47	5

See also

### VARIANTS

**9MOVL**

### DESCRIPTION

Low safety shoes.  
 Bi-material black upper with breathable textile, synthetic and reflective inserts.  
 Breathable 3D mesh inner lining.  
 Cleanliness insole by preformed EVA.  
 Nitrile rubber outsole. EVA Midsole.  
 Anti-puncture midsole in 1100N textile.  
 Safety shoe cap in 200J aluminium.  
 Sizes: 38/47.  
 Comply with the requirements of the norm EN ISO 20345:2011 S3 SRA

### SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

### APPLICATIONS

Luggage handler,  
 Delivery driver, ...

## TECHNICAL FEATURES

<b>Color</b>	Black	<b>Closing</b>	Lacing closure
<b>Color 2</b>	Yellow	<b>Lining</b>	Breathable 3D mesh
<b>Upper</b>	Full grain leather / Polyamide mesh		
<b>Toecap</b>	Aluminium		
<b>Puncture resistant sole</b>	Textile		
<b>Midsole</b>	EVA		
<b>Outsole</b>	Rubber nitrile		
<b>Insole</b>	removable, textile and cushioned foam		
<b>Main assembly</b>	Cemented		

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00367558-Issue 2**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP

MAJ 14/12/2021