

Ref. **9MOOL**

Specialties

Low

Low shoes



The +

- * Lightweight for use all day long.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9MOOL35	35	10
9MOOL36	36	10
9MOOL37	37	10
9MOOL38	38	10
9MOOL39	39	10
9MOOL40	40	10
9MOOL41	41	10
9MOOL42	42	10
9MOOL43	43	10
9MOOL44	44	10
9MOOL45	45	10
9MOOL46	46	10
9MOOL47	47	10
9MOOL48	48	10

Some sizes may only be available in certain countries

DESCRIPTION

The MOON safety shoe is a breathable PU microfibre model, lined with breathable mesh for maximum comfort throughout the day. This metal-free safety shoe guarantees that your foot is well protected while retaining its lightness thanks to its composite toe cap. Equipped with a non-slip sole and a shock absorbing heel, this model provides great stability for its wearer.

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	White	Main assembly	Injected
Color 2	Grey	Closing	Lacing closure
Weight	442 g	Lining	Breathable 3D mesh
Upper	Microfiber		
Toecap	Composite		
Midsole	PU		
Outsole	PU		
Insole	Attached, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/23/1933

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance