

Ref. **9PAR120**

Indoor and dry environments

Low

Low shoes



The +

- \*Quick clip-in.
- \*Ultra-adjusted footwear.
- \*PU2D injected outsole: comfort and adherence.

### PURCHASE PACKAGING

Ref.	Size	Carton
9PAR120038	38	6
9PAR120039	39	6
9PAR120040	40	6
9PAR120041	41	6
9PAR120042	42	6
9PAR120043	43	6
9PAR120044	44	6
9PAR120045	45	6
9PAR120046	46	6
9PAR120047	47	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

PARAIBA is a low safety shoe inspired by the sport universe. Its upper made of polyester mesh provides good breathability. Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. PARAIBA features a toe-cap and an anti-penetration plate made of composite for optimal protection. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

### SECTORS

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Midnight blue	Main assembly	Injected
Weight	538 g	Lining	Breathable 3D mesh
Upper	Mesh		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/20/2750EXT04/11/20

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

SRC

COVERPERF - Damping



## Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.