

Ref. **9PEAL**

Outdoor

Low

Low shoes



The +

- * Footbridge supplying torsional rigidity.
- * Heel scuff cap.
- * Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|---------|------|--------|
| 9PEAL38 | 38 | 10 |
| 9PEAL39 | 39 | 10 |
| 9PEAL40 | 40 | 10 |
| 9PEAL41 | 41 | 10 |
| 9PEAL42 | 42 | 10 |
| 9PEAL43 | 43 | 10 |
| 9PEAL44 | 44 | 10 |
| 9PEAL45 | 45 | 10 |
| 9PEAL46 | 46 | 10 |
| 9PEAL47 | 47 | 10 |

Some sizes may only be available in certain countries

See also

VARIANTS



9PEAH

DESCRIPTION

The PEARL is a low safety shoe in full grain leather lined with a breathable mesh providing a better comfort of use.

For more protection, reinforcements can be found on the front and back of the model. Its non-slip sole is resistant to slipping on steel and ceramic floors.

Thanks to its composite shell and textile anti-perforation sole, this safety shoe is lightweight, flexible and non-magnetic.

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

APPLICATIONS

- Builder,
- Slater,
- Ramp agent,
- Luggage handler,
- Site supervisor,
- Docker, ...

TECHNICAL FEATURES

| | | | |
|-------------------------|-------------------------------------|---------------|-----------------------------|
| Color | Black | Insole | Removable, textile and foam |
| Color 2 | Orange | Main assembly | Injected |
| Weight | 604 g | Closing | Lacing closure |
| Upper | Full grain leather / Polyamide mesh | Lining | Breathable 3D mesh |
| Toecap | Composite | Defined heel | |
| Puncture resistant sole | Textile | | |
| Midsole | PU | | |
| Outsole | PU | | |

INSTRUCTION FOR USE AND STORAGE

Instructi-ons for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/09/24/2216 Ext 01/09/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance