

Ref. **9PYRO**

Outdoor

High

Boots



### The +

- \*Heel and toe Stark scuff caps.
- \*Cushioned insole.
- \*Footbridge supplying torsional rigidity.

#### PURCHASE PACKAGING

Ref.	Size	Carton
9PYRO37	37	5
9PYRO38	38	5
9PYRO39	39	5
9PYRO40	40	5
9PYRO41	41	5
9PYRO42	42	5
9PYRO43	43	5
9PYRO44	44	5
9PYRO45	45	5
9PYRO46	46	5
9PYRO47	47	5

*Some sizes may only be available in certain countries*

#### DESCRIPTION

Safety boot in full leather finished Pull up, water repellent Two side tabs on the upper so they can be pulled on easily. Dual density PU sole (wear layer = 1,1 and comfort layer = 0,65) with shock absorbing PU and reinforcement in the front for better protection. Non-metallic anti-perforation interlayer.

#### SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

#### APPLICATIONS

Builder,  
Slater,  
Ramp agent,  
Luggage handler,  
Site supervisor,  
Dockers, ...

## TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and cushioned foam
Weight	724 g	Main assembly	Injected
Upper	Pull-up leather	Lining	Faux fur
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0870 EXT 01/05/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)

RETAILER STAMP

MAJ 26/09/2022