

Ref. **9RESL10**

Multipurpose

Low

Low shoes



The +

- *Soft PU/PU outsole: cushioning and comfort.
- *Raised heel: stability on ladders.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *3D structured mesh upper: high abrasion resistance (laboratory tested).

PURCHASE PACKAGING

Ref.	Size	Carton
9RESL10035	35	6
9RESL10036	36	6
9RESL10037	37	6
9RESL10038	38	6
9RESL10039	39	6
9RESL10040	40	6
9RESL10041	41	6
9RESL10042	42	6
9RESL10043	43	6
9RESL10044	44	6
9RESL10045	45	6
9RESL10046	46	6
9RESL10047	47	6
9RESL10048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW RESIST is a lightweight, flexible and highly abrasion resistant safety sneaker.

This model has a resistant structured mesh upper, tested in a certified laboratory (CTC).

Its low density PU/PU outsole ensures all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Light blue	Insole	PU Foam, removable, with shock absorber
Color 2	Dark grey	Reinforcement location	Front
Weight	545 g	Lining	Breathable 3D mesh
Upper	Mesh	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/22/1303

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole


SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.