

Ref. **9SWIH10**

Multipurpose

High

High shoes



The +

- *Soft PU/PU outsole: cushioning and comfort.
- *Raised heel: stability on ladders.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *Polyester upper mesh: excellent breathability (laboratory tested).

PURCHASE PACKAGING

Ref.	Size	Carton
9SWIH10035	35	6
9SWIH10036	36	6
9SWIH10037	37	6
9SWIH10038	38	6
9SWIH10039	39	6
9SWIH10040	40	6
9SWIH10041	41	6
9SWIH10042	42	6
9SWIH10043	43	6
9SWIH10044	44	6
9SWIH10045	45	6
9SWIH10046	46	6
9SWIH10047	47	6
9SWIH10048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW SWIFT is a lightweight, flexible and breathable safety sneaker. With a polyester upper and nubuck reinforcement, CLAW SWIFT ensures optimal breathability and durability in dry environments. Its low density PU/PU outsole guarantees all day comfort. Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Yellow	Insole	PU Foam, removable, with shock absorber
Color 2	Black	Reinforcement location	Front
Weight	640 g	Lining	Breathable 3D mesh
Upper	Polyester mesh	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/22/1303 EXT 03/07/22

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Breathability



Shoes tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 4g/h.

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.