

Ref. **9TARN**

Outdoor

High

High shoes



PURCHASE PACKAGING

Ref.	Size	Carton
9TARN35	35	10
9TARN36	36	10
9TARN37	37	10
9TARN38	38	10
9TARN39	39	10
9TARN40	40	10
9TARN41	41	10
9TARN42	42	10
9TARN43	43	10
9TARN44	44	10
9TARN45	45	10
9TARN46	46	10
9TARN47	47	10
9TARN48	48	10

Some sizes may only be available in certain countries

DESCRIPTION

- * metal-free, certified against cold (CI) protective boots with fake fur lining against cold, with strong cowhide uppers
- * antistatic, oil- and acid-proof, SRC no-slip, flexible, double-layer PU soles, mud-proof sole pattern
- * composite plastic toe guard

SECTORS

Regional/public authorities

Maintenance

DIY

TECHNICAL FEATURES

Color	Black	Insole	Comfortable, removable, absorbent insole
Color 2	Green	Main assembly	Injected
Upper	Grain leather	Front bumper	
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Faux fur
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These over-shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the over-shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the over-shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00374128

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)

RETAILER STAMP

MAJ 07/11/2022