

Ref. **U6946**

Indoor and dry environments

Low

Sandals



S1P



The +

Extra large sizes  
ESD compliant safety footwear  
Stabilizing uvex anti-twist heel stiffener

### PURCHASE PACKAGING

Ref.	Size	Carton
6946240	40	
6946241	41	
6946242	42	
6946243	43	
6946244	44	
6946245	45	
6946246	46	
6946342	-	
6946344	-	
6946345	-	

*Some sizes may only be available in certain countries*

### DESCRIPTION

- \* Made of breathable micro velour material breathable upper, sporty design
  - \* Dual, individually adjustable velcro straps
  - \* Steel nose reinforcement and puncture-resistant steel soleplate
  - \* Two-layer polyurethane outsole for excellent slip resistance (SRC)
  - \* Complies with ESD requirements: temporary Transition resistance less than 35 megaohms
  - \* Stabilizing uvex anti-twist heel stiffener with for protection against ankle twisting
  - \* Foam nose protector, width 11, absorbent mesh lining
  - \* Reflective elements, uvex climazone foot climate control,
  - \* Replaceable, anti-static and comfortable with moisture-wicking system and with additional cushioning at the heel and toe front of the foot
- Size: 38-52

SECTORS

APPLICATIONS

## TECHNICAL FEATURES

Color	Black	Insole	Replaceable, antistatic and comfortable insole with moisture extraction system
Color 2	Grey		
Upper	Microfiber		
Toecap	Steel	Main assembly	Injected
Puncture resistant sole	Stainless steel	Closing	Scratch closure
Midsole	PU	Lining	Moisture wicking non-woven membrane
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)