

Ref. **U6949**

Multipurpose

Low

Low shoes



S2



The +

- * very good wearing comfort
- * replaceable, antistatic and comfortable insole with moisture wicking system
- * reflective elements

PURCHASE PACKAGING

Ref.	Size	Carton
6949838	38	
6949839	39	
6949840	40	
6949841	41	
6949842	42	
6949843	43	
6949844	44	
6949845	45	
6949846	46	
6949847	47	

Some sizes may only be available in certain countries

DESCRIPTION

- Breathable upper made of microvelur material
- * Steel toecap
 - * Two-layer polyurethane sole with excellent non-slip (SRC)
 - * Sporty design with ESD feature
 - * uvex anti-twist rear brace for ankle protection

SECTORS

Manufacture of electrical and electronic equipment and machines

Regional/public authorities

Maintenance

Infrastructure, building industry

Construction - finishing work

DIY

APPLICATIONS

medium heavy outdoor application

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Color 2	Grey	Lining	Moisture wicking non-woven membrane
Upper	Full grain leather / Microfiber	Defined heel	
Toecap	Steel		
Midsole	PU		
Outsole	PU		
Insole	replaceable, antistatic and comfortable insole with moisture extraction system		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EPI CAT. II

EN ISO 20345:2011

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol