

Ref. **U84012**

Outdoor

High

High shoes



S3



PURCHASE PACKAGING

| Ref. | Size | Carton |
|---------|------|--------|
| 8401238 | - | |
| 8401239 | - | |
| 8401240 | 40 | |
| 8401241 | 41 | |
| 8401242 | 42 | |
| 8401243 | 43 | |
| 8401244 | 44 | |
| 8401245 | 45 | |
| 8401246 | 46 | |
| 8401247 | - | |
| 8401248 | - | |
| 8401249 | - | |
| 8401250 | - | |

Some sizes may only be available in certain countries

SECTORS

Mechanicals constructions

Light Industries

Manufacture of electrical and electronic equipment and machines

Regional/public authorities

Maintenance

Infrastructure, building industry

Construction - finishing work

TECHNICAL FEATURES

| | | | |
|---------------|--|-------------------------|--------------------|
| Color | Black | Reinforce-ment location | Front |
| Upper | Full grain leather | Closing | Lacing closure |
| Midsole | PU | Lining | Breathable 3D mesh |
| Outsole | PU | Defined heel | |
| Insole | antibacterial, skin neutral, removable antistatic insoles with moisture-control system ensuring excellent feet climate | | |
| Main assembly | Injected | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes

STANDARD(S)



EPI CAT. I

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol